



GPI12202018

MARKSMAN[™]750

Cans | Bottles | PET

The MM750 is a wrap forming machine for moderate speeds, packaging multiple diameters and heights of cans or glass and plastic bottles in basic over the crown or neck through wraps.

Machine Features

Standard

- GPI standard lock
- Dual rotary vane vacuum pump
- Automatic oil system
- Automatic grease system
- 19" (0.5m) 750 carton gravity magazine
- 3 arm rotary

Frame

· Stainless steel frame with corrosion resistant components

Guards

• Full height, clear hinged guard doors providing easy walk-in access to the machine functions for changeover and maintenance

Optional

- Powered magazines with capacities of 2.800, 5.000, 10.000 cartons
- Lock inspection w/wo pack reject
- Venturi vacuum generator

Changeover

No-tool changeovers are quick, simple and repeatable Time

30 minutes (format change) 45 minutes (product / change)

Specifications

Standard Machine Elevation 41-3/8" +/- 2" (1050mm +/-50mm)

Machine Weight Approx. 10,000 lbs (4500 kg)

Air Requirements 80psi - 1 SCFM

(6 bar - 2 m3/h)

Electrical 400/460 VAC 50/60 Hz

Main Drive Motors

AC Gearmotor

Package Closing System **GPI Lock System**

(.508m)

4'6"

(1.37m)

7'-2 11/32' (2.2m)


Primary Container Size Ranges

Bottles, glass and plastic Cans (2 piece and 3 piece) Cups, pharmaceuticals, aerosols, etc.

Diameter: 1.69" (43mm) to 2.95" (75mm) Height: 3.94" (100mm) to 11.02" (280mm)

Pack Formats

Standard: 2x2, 2x3 Optional 2x4, 2x5, 1x2, 1x3, 1x4. 1x5



Pack Styles

Standard: Over the crown, no top, straight

Optional: Ad-panel, full tuck adpanel, bottle guard, handle wrap, top and bottom gussets on cans

Speed / Pitches

Packages Cans at speeds up to:				
Pitch	Line	Surge		
10"	180ppm	200ppm		
(standard)				
12"	140ppm	160ppm		
15"	105ppm	125ppm		
* Speeds for glass bottles reduced 15%				

19'-7 7/64" (5.97m) INSTALLED LENGTH BETWEEN CUSTOMER SUPPLIED CONVEYORS

14'-0" (4.26m)



5'-7 7/64*

(1.7m)

Graphic Packaging International 1500 Riveredge Parkway NW, #100 Atlanta, GA 30328 +1 (770) 240-7200

Please visit our website at graphicpkg.com for more information. © Copyright 2018, Graphic Packaging International. All rights reserved.

MARKSMAN[™]750S Cans | Bottles | PET

Similar to the larger MM750, the MM750S is a wrap forming machine for moderate speeds, packaging multiple diameters and heights of cans or glass and plastic bottles in basic over the crown or neck through wraps. This machine has been shortened to fit within limited factory floorplans.

Machine Features

Standard

- GPI standard lock
- Dual rotary vane vacuum pump
- Automatic oil system
- 19" (0.5m) 750 carton gravity magazine
- 3 arm rotary

Frame

· Stainless steel frame with corrosion resistant components

Guards

• Full height, clear hinged guard doors providing easy walk-in access to the machine functions for changeover and maintenance

Optional


- Powered magazines with capacities of 2,800, 5,000, 10,000 cartons
- Lock inspection w/wo pack reject
- Venturi vacuum generator


Changeover

No-tool changeovers are guick, simple and repeatable

Time

30 minutes (format change) 45 minutes (product / change)





Specifications

Standard Machine Elevation 41-3/8" +/- 2" (1050mm +/-50mm)

Machine Weight Approx. 8,800 lbs (4,000 kg)

Air Requirements 80psi - 1 SCFM (6 bar - 2 m3/h)

Electrical 400/460 VAC 50/60 Hz

Main Drive Motors AC Gearmotor

Package Closing System

GPI Lock System

Ancillary Equipment

Turner / Divider / Reject Units


Primary Container Size Ranges

Bottles, glass and plastic Cans (2 piece and 3 piece) Cups, pharmaceuticals, aerosols, etc.

Diameter: 1.69" (43mm) to 2.95" (75mm) Height: 3.94" (100mm) to 11.02" (280mm)

Pack Formats Standard: 2x2, 2x3 Optional 2x4, 2x5, 1x2, 1x3, 1x4. 1x5

MM750S ▲ ➡ LANES



Pack Styles

Standard: Over the crown, No top, straight

Optional: Ad-panel, full tuck adpanel, bottle guard, handle wrap, top and bottom gussets on cans

Speed / Pitches

Packages Cans at speeds up to:			
Pitch	Line	Surge	
10"	180ppm	200ppm	
(standard)			

* Speeds for glass bottles reduced 15%



Graphic Packaging International 1500 Riveredge Parkway NW, #100 Atlanta, GA 30328 +1 (770) 240-7200

Please visit our website at graphicpkg.com for more information. © Copyright 2018, Graphic Packaging International. All rights reserved.

MARKSMAN 750TL Cans | Bottles | PET

Similar to the MM750, the MM750TL is a wrap forming machine for moderate speeds, packaging multiple diameters and heights of cans or glass/plastic bottles in basic over the crown or neck through wraps. This machine has been lengthened to allow inclusion of the Tab-Locker folding module. This machine also includes more robust side lugs allowing speeds up to 200ppm on glass bottles.

Machine Features

Standard

- GPI standard lock
- Dual rotary vane vacuum pump
- Automatic oil system
- Automatic grease system
- IQ Tablet
- 19" (0.5m) 750 carton gravity magazine
- 3 arm rotary

Frame

Stainless steel frame with corrosion resistant components

Guards

• Full height, clear hinged guard doors providing easy walk-in access to the machine functions for changeover and maintenance

Optional

- Powered magazines with capacities of 2,800, 5,000, 10,000 cartons
- Lock inspection w/wo pack reject
- Venturi vacuum generator


Changeover


No-tool changeovers are quick, simple and repeatable

Time

30 minutes (format change)45 minutes (product / change)

Machine Footprint







Graphic Packaging International 1500 Riveredge Parkway NW, #100 Atlanta, GA 30328 +1 (770) 240-7200

Primary Container Size Ranges


Bottles, glass and plastic Cans (2 piece and 3 piece) Cups, pharmaceuticals, aerosols, etc.

Diameter: 1.69" (43mm) to 2.95" (75mm) Height: 3.94" (100mm) to 11.02" (280mm)

Pack Formats

Standard: 2x2, 2x3 Optional 2x4, 2x5, 1x2, 1x3, 1x4. 1x5

MM750TL



Pack Styles

Standard: Over the crown, no top, straight

Optional: Ad-panel, full tuck adpanel, bottle guard, handle wrap, top and bottom gussets on cans

Speed / Pitches

Line	Surge			
180ppm	200ppm			
(standard)				
140ppm	160ppm			
105ppm	125ppm			
*Speeds for glass bottles reduced 15%				
	180ppm rd) 140ppm 105ppm			

Please visit our website at graphicpkg.com for more information. © Copyright 2018, Graphic Packaging International. All rights reserved.

Specifications

Standard Machine Elevation 41-3/8" +/- 2" (1050mm +/-50mm)

Machine Weight Approx. 11,000 lbs (5,000 kg)

Air Requirements 80psi - 1 SCFM (6 bar - 2 m3/h)

Electrical

400/460 VAC 50/60 Hz

Main Drive Motors AC Gearmotor

Package Closing System

GPI Lock System Tab Locker