









The QuikFlex[™] 10 is Graphic Packaging's compact, simple and economical manual packaging system for fully-enclosed cartons. Cartons are sealed as a single operator pushes packs through the patented locking system that uses no power or glue. The QuikFlex[™] 10 is changeover ready and supports a variety of container sizes and pack formats.

Machine Features

Standard

• GPI Custom Targeteer Lock

Frame

 Stainless Steel Frame / Corrosion Resistant Construction

Guards

 Not required as this is a manually operated machine with no inherent dangers

Optional

- · Infeed Table
- Discharge Chute
- Discharge Table
- RH or LH configurations possible at time of the order

Changeover

Simple changeover to a variety of heights and diameters of various products. Changeover time is 5-10 minutes using scales and pointers.

Floorplan

Right Hand Machine Pictured

(.980m)

Specifications

Standard Machine Elevation

Machine Weight

Approx. 400lbs (181 kg)

Air Requirements

None Required

Electrical

None Required

Glue

None Required

Ancillary Equipment

- Custom Can Supply System
- · Custom Discharge Conveyor

Pack Formats

- 2x2, 2x3, 2x4, 2x5, 2x6
- 3x3, 3x4, 3x5, 3x6
- 4x4, 4x5, 4x6



Primary Container Size Ranges

All known beverage cans and bottles.

Diameter:

53mm to 66mm
67mm to 79mm
80mm to 99mm
2x2 4x6*
4x5*
2x2 4x4*

*Largest Format Possible

Height (All Beverage Cans)

88mm to 194mm Other Product Types and Sizes Possible (Check with GPI Contact)

Pack Styles

- Fully Enclosed—Lock Closure
- Cooler Pack—Lock Closure



Speed

5-20 Packs Per Minute

