







MARKSMAN[™]70

Cans | Bottles | PET

A low speed, fully automatic wrap packaging machine occupying minimal floor space. Capable of being adjusted to multiple diameter and height ranges for cans, glass and PET bottles.

Specifications

Machine Weight

Air Requirements

80psi - 4 SCFM

(6 bar - 7 m3/h)

400/460 VAC

AC Gearmotor

Turner / Divider

Changeover

Time

adjustments required.

Main Drive Motors

Ancillary Equipment

Tool, hand knob and handwheel

5-15 minutes, depending on package

Electrical

50/60 Hz

Standard Machine Elevation

Approx. 6,600 lbs (3,000 kg)

41-3/8"+/-2" (1050mm +/-50mm)

Machine Features

Standard

- GPI standard lock
- Venturi vacuum generator
- Automatic oil system
- Starwheels and selector chains
- 19" (0.5m) 750 carton gravity magazine
- Reciprocating arm feeder

Frame

Stainless steel frame with corrosion resistant components


Guards


• Full height, clear hinged guard doors providing access to the machine functions for changeover and maintenance

Optional

- Powered magazine with capacity of 2,800 cartons
- Accessible lube points
- Automatic oil
- Rotary vane vacuum pump

Machine Footprint





Graphic Packaging

Graphic Packaging International 1500 Riveredge Parkway NW, #100 Atlanta, GA 30328 +1 (770) 240-7200


Primary Container Size Ranges

Bottles, glass and plastic Cans (2 piece and 3 piece) Cups, pharmaceuticals, aerosols, etc.

Diameter: 1.69" (43mm) to 2.95" (75mm) Height: 3.94" (100mm) to 11.02" (280 mm)

Pack Formats

Standard: 2x2, 2x3 Optional: 2x4, 2x5, 1x2, 1x3, 1x4, 1x5



Pack Styles

- Standard: Over the crown, neck through, straight
- Optional: Ad-panel, Handle Wrap



Speed / Pitches

Forms Packages at speeds up to:

Pitch	Line	Surge	
10"	60ppm	70ppm	(standard)

Please visit our website at graphicpkg.com for more information. © Copyright 2018, Graphic Packaging International. All rights reserved.